

Safety Data Sheet

Product :

Nitrous oxide (refrigerated)

Page :1/5

MSDS Nr : 093B_AL

Version : 1.01

Date : 31/07/2002

1 IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY

MSDS Nr	093B_AL
Product name	Nitrous oxide (refrigerated)
Chemical formula	N ₂ O
Company identification	see heading and/or footer see paragraph 16 "OTHER INFORMATION"
Emergency phone numbers	see heading and/or footer see paragraph 16 "OTHER INFORMATION"

2 COMPOSITION/INFORMATION ON INGREDIENTS

Substance/Preparation	Substance.
Components/Impurities	Contains no other components or impurities which will influence the classification of the product.
CAS Nr	10024-97-2
EEC Nr (from EINECS)	233-032-0

3 HAZARDS IDENTIFICATION

Hazards identification	Refrigerated liquefied gas. Contact with product may cause cold burns or frostbite. Oxidant. Strongly supports combustion. May react violently with combustible materials.
------------------------	---

4 FIRST AID MEASURES

Inhalation	In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of co-ordination. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.
Skin/eye contact	Immediately flush eyes thoroughly with water for at least 15 minutes. In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance
Ingestion	Ingestion is not considered a potential route of exposure.

Safety Data Sheet

Product :

Nitrous oxide (refrigerated)

Page :2/5

MSDS Nr : 093B_AL

Version : 1.01

Date : 31/07/2002

5 FIRE FIGHTING MEASURES

Specific hazards	Supports combustion. Exposure to fire may cause containers to rupture/explode. Non flammable
Hazardous combustion products	If involved in a fire the following toxic and/or corrosive fumes may be produced by thermal decomposition: Nitric oxide/nitrogen dioxide
Suitable extinguishing media	All known extinguishants can be used.
Specific methods	If possible, stop flow of product. Move away from the container and cool with water from a protected position. If leaking do not spray water onto container. Water surrounding area (from protected position) to contain fire.
Special protective equipment for fire fighters	Use self-contained breathing apparatus and chemically protective clothing.

6 ACCIDENTAL RELEASE MEASURES

Personal precautions	Evacuate area. Ensure adequate air ventilation. Eliminate ignition sources. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Use protective clothing.
Environmental precautions	Try to stop release. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
Clean up methods	Ventilate area. Keep area evacuated and free from ignition sources until any spilled liquid has evaporated. (Ground free from frost).

7 HANDLING AND STORAGE

Handling and storage	Use no oil or grease. Open valve slowly to avoid pressure shock. Segregate from flammable gases and other flammable materials in store. Suck back of water into the container must be prevented. Do not allow backfeed into the container. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
----------------------	---

Safety Data Sheet

Product :

Nitrous oxide (refrigerated)

Page :3/5

MSDS Nr : 093B_AL

Version : 1.01

Date : 31/07/2002

Keep away from ignition sources (including static discharges).

Refer to supplier's container handling instructions.

Keep container below 50°C in a well ventilated place.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure limit value -TLV(ACGIH)	50 ppm (2000 edition)
Exposure limit value for country	Germany: MAK= 100 ppm
Personal protection	Do not smoke while handling product. Ensure adequate ventilation. Protect eyes, face and skin from liquid splashes.

9 PHYSICAL AND CHEMICAL PROPERTIES

Molecular weight	44
Melting point	-90.81 °C
Boiling point	-88.5 °C
Critical temperature	36.4 °C
Relative density, gas	1.5 (air=1)
Relative density, liquid	1.2 (water=1)
Vapour Pressure 20°C	50.8 bar
Solubility mg/l water	2.2 mg/l
Appearance/Colour	Colourless liquid
Odour	Sweetish Poor warning properties at high concentrations.
Autoignition temperature	Not applicable
Flammability range	Oxidiser.
Other data	Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

10 STABILITY AND REACTIVITY

Stability and reactivity	May react violently with combustible materials May react violently with reducing agents. Violently oxidises organic material. Thermal decomposition yields toxic products which can be corrosive in the presence of moisture. At temperatures over 575°C and at atmospheric pressure, nitrous oxide decomposes into nitrogen and oxygen. Pressurized nitrous oxide can also decompose at temperatures equal or
--------------------------	--

Safety Data Sheet

Product :

Nitrous oxide (refrigerated)

Page :4/5

MSDS Nr : 093B_AL

Version : 1.01

Date : 31/07/2002

greater than 300°C. In the presence of catalysts (e.g. halogen products, mercury, nickel, platinum) the rate of decomposition increases and decomposition can occur at even lower temperatures. Nitrous oxide dissociation is irreversible and exothermic, leading to a considerable rise in pressure.

Liquid spillages can cause embrittlement of structural materials.

11 TOXICOLOGICAL INFORMATION

General

No known toxicological effects from this product.

12 ECOLOGICAL INFORMATION

General

Can cause frost damage to vegetation.

When discharged in large quantities may contribute to the greenhouse effect.

Global warming factor

310

13 DISPOSAL CONSIDERATIONS

General

To atmosphere in a well ventilated place.

Do not discharge into any place where its accumulation could be dangerous.

Contact supplier if guidance is required.

Discharge to atmosphere in large quantities should be avoided.

14 TRANSPORT INFORMATION

Proper shipping name

Nitrous oxide, refrigerated liquid

UN Nr

2201

Class/Div

2.2

Subsidiary risk

5.1

ADR/RID Classification code

2, 3°O

ADR/RID Hazard Nr

225

Labelling ADR

Label 05: fire intensifying risk.

Label 2: non flammable non toxic gas

Other transport information

Avoid transport on vehicles where the load space is not separated from the driver's compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

Before transporting product containers ensure that they are firmly secured and:

Safety Data Sheet

Product :

Nitrous oxide (refrigerated)

Page :5/5

MSDS Nr : 093B_AL

Version : 1.01

Date : 31/07/2002

- there is adequate ventilation.
- compliance with applicable regulations.

15 REGULATORY INFORMATION

Number in Annex I of Dir 67/548

Not included in Annex I.

EC Classification

Proposed by the industry

-Symbols

O;R8

-Risk phrases

O: Oxidising

-Safety phrases

R8 Contact with combustible material may cause fire.

S9 Keep container in well ventilated place.

S17 Keep away from combustible material.

S36 Wear suitable protective clothing.

16 OTHER INFORMATION

Asphyxiant in high concentrations.

May cause frostbite.

The hazard of asphyxiation is often overlooked and must be stressed during operator training.

Ensure all national/local regulations are observed.

Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

This Safety Data Sheet has been established in accordance with the applicable European Directives and applies to all countries that have translated the Directives in their national laws.

This MSDS is for information purposes only and is subject to change without notice. [Prior to purchase of products, please contact your local Air Liquide office for a complete MSDS (with Manufacturer's name and emergency phone number).]

End of document.

Number of pages :5